

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE CLAIMS

Amend claims 1-9 as shown:

1. (Amended) A method for [synchronising] synchronizing data between a receiving computer and a sending computer, wherein the sending computer has a source file and the receiving computer has a reference file and the receiving and sending computers are coupled for communication therebetween by way of a communications link or network, the method comprising [the steps of]:

i) arranging the source file at the sending computer into a sequence of data blocks, each block comprising a predetermined number of contiguous data units, and computing a source key value for each block in the source file;

ii) transmitting the source key values from the sending computer to the receiving computer;

iii) at the receiving computer, comparing the source key values with reference key values computed for [each] respective blocks comprising a predetermined number of contiguous data units in the reference file to determine matches between source key values and reference key values;

iv) communicating from the receiving computer to the sending computer an indication of which source keys do not have matching reference keys, and transmitting

data blocks from the source file corresponding to the unmatched source keys from the sending computer to the receiving computer; and

v) constructing at the receiving computer a target file from the contiguous data units in the reference file determined to have reference key values matching respective source key values and the data blocks from the source file received from the sending computer wherein the constructed target file at the receiving computer is [synchronised] synchronized with the source file at the sending computer.

2. (Amended) A method as [claimed] in claim 1, wherein the source key values for the sequence of source file data blocks are pre-computed and stored for subsequent use.

3. (Amended) A method as [claimed] in claim 2, wherein:

the sending computer and receiving computer are coupled to communicate by way of an intervening computer containing a cache memory, and [wherein]

a copy of the source key values are stored in the intervening computer cache memory and provided therefrom to the receiving computer.

4. (Amended) A method for constructing a target data file at a first computer from a reference file stored at the first computer and a source file at a remote second computer such that the constructed target file is [synchronised] synchronized with the source file, said method comprising [the steps of]:

- i) requesting and receiving from the remote second computer a source file summary comprising a sequence of source key values being codes derived from data blocks of predetermined length making up the source file;
- ii) generating [a] reference key values for [each] respective contiguous portions of the reference file of predetermined length and comparing the reference key values with the received source key values, to determine matches therebetween;
- iii) requesting and receiving from the remote second computer those data blocks from the source file for which no match was found between the corresponding source key value and the reference key values; and
- iv) constructing a target data file from the received source file data blocks and those contiguous portions of the reference file for which the corresponding reference key value was found to match a source key value, wherein the constructed target file is [synchronised] synchronized with the source file.

5. (Amended) A method as [claimed] in claim 4, wherein:

the first and second computers are coupled to communicate over a computer network including a proxy computer which is closer or more conveniently located to communicate with the first computer than is the second computer, and [wherein the step of]

requesting and receiving the source file summary includes providing the source file summary to the first computer from a copy of the source file summary generated at the second computer and previously received and stored by the proxy computer.

6. (Amended) A method as [claimed] in claim 5, wherein [the step iii) of] requesting and receiving data blocks for which no match was found includes providing those data blocks to the first computer from the proxy computer from a copy of the source file data blocks previously provided from the second computer and stored in a cache memory at the proxy computer.

7. (Amended) In a computer network having a sending computer, a receiving computer and at least one proxy computer, wherein the sending computer has a source file and the receiving computer has a reference file and the receiving, sending and a proxy computer are coupled for communication therebetween by way of said network, a method for synchronizing [synchronising] data between the receiving computer and the sending computer, the method comprising [the steps of]:

i) arranging the source file at the sending computer into a sequence of data blocks, each block comprising a predetermined number of data units, and computing a source key value for each block in the source file;

ii) transmitting the source key values from the sending computer to the receiving computer;

iii) at the receiving computer, comparing the source key values with reference key values computed for [each] respective blocks comprising a predetermined number of contiguous data units in the reference file to determine matches between source key values and reference key values;

iv) communicating from the receiving computer to the sending computer or proxy computer an indication of which source keys do not have matching reference keys, and transmitting data blocks from the source file corresponding to the unmatched source keys from the sending computer or proxy computer to the receiving computer; and

v) constructing at the receiving computer a target file from the contiguous data units in the reference file determined to have reference key values matching respective source key values and the data blocks from the source file received from the sending computer wherein the constructed target file at the receiving computer is [synchronised] synchronized with the source file at the sending computer.

8. (Amended) A method as [claimed] in claim 7, wherein [the step of] transmitting the source key values from the sending computer to the receiving computer includes storing a copy of the source key values in a cache at the proxy computer and transmitting the source key values from the proxy computer to the receiving computer on request.

9. (Twice Amended) A method as [claimed] in claim 7 wherein:

a copy of at least some of the source file data blocks are transmitted from the sending computer and stored in a cache at the proxy computer; and [wherein the step of]

transmitting data blocks from the source file includes transmitting said data blocks form the proxy computer cache copy to the receiving computer.